



Camera Inspection System // Type EOK-PQ



Technical Data

Description

- Color Classes and blister sizes are easy to manage
- Powerful analysis of the print image
- Taught-in print images are displayed
- Formats can be changed quickly and easily
- Integrated shift register
- Integrated password/user administration with 4 user levels
- Biometric user management
- If packaging layout doesn't change, existing formats can be easily modified to be used with a new format
- The last 100 „bad pictures“ are saved
- Significant evaluation statistics with detailed information
- Easy operation under Windows 7 with comprehensive and video assisted help support
- Simple teach-in procedure with automatic search and find function for all colors and attributes of the print image
- No unwanted glare when illuminating the foil and the print image
- Very high rate of evaluation
- Well-arranged display of results
- Also suitable for retrofitting

Resolution camera

1392 x 1040 px
 1628 x 1236 px
 2452 x 2056 px

Supply voltage

24 VDC
 power supply is delivered according to configuration

Dimensions

Depends on machine or unit to be fitted with the inspection system, foil width and index

Pic. 1) Camera housing with LEDs

Pic. 2) Fanless LED lightning

Pic. 3) Fingerprint scanner



HPF is a member of:



**SINCE 1980
 EVERYTHING
 UNDER
 CONTROL**



HPF ELEKTRONIK

Hans P. Friedrich Elektronik GmbH
 Neumuehleweg 34
 73660 Urbach // Germany

Fon +49 (0)7181 99887-0
 Fax +49 (0)7181 99887-9

Mail info@hpf-elektronik.de
 Web www.hpf-elektronik.de

